

1. PRODUCT INFORMATION

➤ **Product Detail:**

Trade Name: **GIBSON PLATINUM FULLY SYNTHETIC ENGINE OIL SAE 5W40 API SM/CF;**

➤ **Manufacturer / Supplier:**

➤ **GIBSON OIL SDN. BHD.**

No. 15, Jalan Bukit 24, Bandar Seri Alam, 81750 Masai, Johor.

2. APPLICATIONS

Naturally can be used for modern gasoline engine and diesel engines in passenger cars and light truck. Low emission passenger car and light duty vehicle engines fitted with latest catalytic converter (gasoline) or diesel particulate filter technology. Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

3. TYPICAL CHARACTERISTICS

➤ **Product Typical:**

No.	Test Item	Test Methods	Test Result	Unit
1	Viscosity, Kinematic, @40°C	ASTM D445	88.6	mm ² /s
2	Viscosity, Kinematic, @100°C	ASTM D445	14.3	mm ² /s
3	Viscosity Index	ASTM D2270	167	-
4	Total Base Number, KOH	SH/T 0251	8.2	mg/g
5	Flash Point	ASTM D92	240	°C
6	Pour Point	ASTM D55950	-40	°C
7	Density, @15°C	ASTM D4052	0.869	kg/L

*The above data represents the typical laboratory value of the product, and the specific parameters are subject to the actual test.