

1. PRODUCT INFORMATION

➤ **Product Detail:**

Trade Name: **GIBSON SUPER 6000 SAE 10W30 API SL/CF**

➤ **Manufacturer / Supplier:**

GIBSON OIL SDN. BHD.

No. 15, Jalan Bukit 24, Bandar Seri Alam, 81750 Masai, Johor.

2. APPLICATIONS

GIBSON Super 6000 SAE 10W30 oil can be used in modern vehicles but commonly is not. Oils containing additives that lower **viscosity** (make it thinner) at lower temperatures are more commonly used.

3. TYPICAL CHARACTERISTICS

➤ **Product Typical:**

No.	Test Item	Test Methods	Test Result	Unit
1	Viscosity, Kinematic, @40°C	ASTM D445	89	mm ² /s
2	Viscosity, Kinematic, @100°C	ASTM D445	11	mm ² /s
3	Viscosity Index	ASTM D2270	109	-
4	Total Base Number, KOH	SH/T 0251	8	mgKOH/g
5	Flash Point	ASTM D92	220	°C
6	Pour Point	ASTM D55950	-26	°C
7	Density, @15°C	ASTM D4052	0.87	kg/L

*The above data represents the typical laboratory value of the product, and the specific parameters are subject to the actual test.