

Products Data Sheets

DOC. NO	GO-PDS-35	
VER. NO	A.3	
PAGE. NO	1/1	

1. PRODUCT INFORMATION

> Product detail :

Trade Name: GIBSON LITHIUIM COMPLEX GREASE XHP-29

- Manufacturer / Supplier :
- GIBSON OIL SDN. BHD.

No.15, Jalan Bukit 24, Bandar Seri Alam, 81750 Masai, Johor.

2. TYPICAL TEST DATA

> Description

Thickened by lithium complex soap, it is made from deeply refined mineral oil with extreme pressure additives, rust and oxidation inhibitors.

Application temperature range: -20 °C~160 °C.

Product typical

Parameter	Soft hardness		Test Method
Parameter	2#	3#	rest Method
Appearance	Dark Blue Smooth	Dark Blue Smooth	Visual
Ingredient	Mineral Oil/ Lithium	Mineral Oil/ Lithium	-
NLGI GRADE NO.	2	3	GB/T 269
Worked Cone Penetration, 0.1mm	265-295	220-250	ASTM D217
Dropping Point, °C	235	240	ASTM D566

^{*}The above data represents the typical laboratory value of the product, and the specific parameters are subject to the actual test.



Tel: +607-3822112 Fax: +607-3824322 E-mail: gibson.mktg@gmail.comWebsite: www.gibsonoil.com