

## 1. PRODUCT INFORMATION

- **Product Detail:**  
Trade Name: **GIBSON SUPER 7000 SAE 20W50 API SL/CF;**
- **Manufacturer / Supplier:**
- **GIBSON OIL SDN. BHD.**  
**No. 15, Jalan Bukit 24, Bandar Seri Alam, 81750 Masai, Johor.**

## 2. APPLICATIONS

Naturally can be used for modern gasoline engine and diesel engines in passenger cars and light truck. Low emission passenger car and light duty vehicle engines fitted with latest catalytic converter (gasoline) or diesel particulate filter technology. Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

## 3. TYPICAL CHARACTERISTICS

- **Product Typical:**

No.	Test Item	Test Methods	Test Result	Unit
1	Viscosity, Kinematic, @40°C	ASTM D445	135.3	mm <sup>2</sup> /s
2	Viscosity, Kinematic, @100°C	ASTM D445	13.3	mm <sup>2</sup> /s
3	Viscosity Index	ASTM D2270	92	-
4	Total Base Number, KOH	SH/T 0251	8	mg/g
5	Flash Point	ASTM D92	240	°C
6	Pour Point	ASTM D55950	-25	°C
7	Density, @15°C	ASTM D4052	0.886	kg/L

\*The above data represents the typical laboratory value of the product, and the specific parameters are subject to the actual test.